

**Warco Premium Lubricants****(MSDS) MATERIAL SAFETY DATA SHEET****WARCO GEAR OIL GL-1 SAE 85W-90****SECTION 1 MATERIAL IDENTIFICATION****PRODUCT – WARCO GEAR OIL GL-1 SAE 85W-90**

NOV 25, 2006

MANUFACTURER

WARCO Products, Inc.  
12505 SW Herman Rd  
Tualatin, OR 97062

PHONE NUMBERS

Emergency (Chemtrec) (800) 424-9300

CHEMICAL FAMILY

Petroleum Hydrocarbon; Blend Stock

CHEMICAL NAME

Mixture

PRODUCT CODE

LAP2147

PRODUCT FAMILY

Gear Oil

CHEMICAL FORMULA

Mixture

CAS NUMBER

Mixture (Refer to Section 2)

SYNONYMS

Gear Oil, Petroleum Lubricating Oil

NFPA CODES

Flammability 1 Reactivity 0 Health 1  
0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme

**SECTION 2****HAZARDOUS  
COMPONENTS**

| <u>Ingredients</u>                                | <u>CAS #</u>                   | <u>WT. %</u> |
|---|--------------------------------|--------------|
| Refined Petroleum Oil(s)<br>Proprietary Additives | Refer to Section 13<br>Mixture | >97<br><3    |

**SECTION 3****SHIPPING INFORMATION**

|                      |                           |
|----------------------|---------------------------|
| Shipping Name        | Petroleum Lubricating Oil |
| Hazard Class         | Non-hazardous liquid      |
| UN Number            | Not Applicable            |
| Proper Shipping Name | Not Applicable            |
| Hazard Label         | Not Applicable            |
| Reportable Quantity  | Not Applicable            |

|                |                |
|----------------|----------------|
| Boiling Point  | Not Determined |
| Vapor Pressure | Not Determined |

**SECTION 4****PHYSICAL DATA**

|                     |                            |
|---------------------|----------------------------|
| Vapor Density       | Not Determined             |
| Solubility in water | Negligible                 |
| Appearance          | Amber liquid               |
| Odor                | Mild petroleum odor        |
| Specific Gravity    | .88 - .90 @ 60°F Water = 1 |
| Evaporation Rate    | Not Determined             |
| Freezing Point      | Not Determined             |
| Viscosity           | 14.5 cST @ 212°F (100°C)   |

## SECTION 5 FIRE AND EXPLOSION HAZARD DATA

**Flash Point** >400°F, 204°C (COC, ASTM D92)

**Auto Ignition**

**Temperature** Not Determined

**Flammable Limits** LEL Not Established  
(% by Volume in Air) UEL Not Established

**Extinguishing Media** CO<sub>2</sub>, dry chemical, foam, or water fog.

Water may be ineffective in fighting an oil fire unless used by experienced fire fighters. Product will float and can be reignited on surface of water.

### Special Fire Fighting Procedures

Evacuate area of all unnecessary personnel. Shut off source, if possible. Use NIOSH/MSHA approved self-contained breathing apparatus and other protective equipment and/or garments described in Section 9 if conditions warrant. Water fog or spray may be used to cool exposed containers and equipment.

For large storage fires involving this material and/or other lubricating products, do not enter any enclosed or confined space without full protective equipment including self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products, and oxygen deficiencies.

**Fire and Explosion Hazards** - Carbon oxides and various hydrocarbons formed when burned. Water may cause frothing.

**SECTION 6****REACTIVITY HAZARD DATA**

|                            |  |
|----------------------------|--|
| <b>Stability</b>           | Stable   |
| <b>Conditions to Avoid</b> | Extreme Heat, open flames or sparks                |
| <b>Incompatibility</b>     | Strong oxidizing agents                            |
| <b>Polymerization</b>      | Hazardous polymerization is not expected to occur. |

**Hazardous Combustion / Decomposition Products**

Carbon oxides and various hydrocarbons formed when burned – traces of sulfur oxides.

**SECTION 7****HEALTH HAZARD DATA****OSHA PEL and ACGIH TVL - Oil Mist, Mineral**

TWA 5mg/M<sup>3</sup>  
STEL 10 mg/M<sup>3</sup> - Ceiling

**Exposure Limits** None established

**Effects of Exposure** See Below

**Inhalation** Not expected to be toxic by inhalation. However, breathing mineral oil mist at levels above the TLV may cause respiratory irritation and possible discomfort. Elevated mists concentrations above applicable workplace exposure levels may cause lung damage. Incidental mists/vapors are the **Major Route of Entry**.

**Ingestion** Generally of a low order of toxicity. Not expected to be a problem when ingested. Upon ingestion of large quantities, slight gastrointestinal discomfort, diarrhea and headache may occur. Small doses may produce irritation and/or diarrhea. If aspirated into the lungs, liquid can cause severe lung damage or death. If uncomfortable seek medical assistance.

**Skin Contact** Material expected to cause no more than minor skin irritation following prolonged and/or repeated contact. Wash contact areas with soap and water.

**Eye Contact** Flush thoroughly with water. If irritation characterized by pain, swelling, redness or blurred vision, call a physician. Contact with heated material may cause thermal burns.

**Injection** Injection under the skin, in muscle or into the blood stream can cause irritation, inflammation, swelling or serious, permanent tissue damage. Seek medical attention immediately.

**Chronic Effects** Prolonged and/or frequent contact may cause drying, cracking (dermatitis) or folliculitis and may cause irritation.

## SECTION 8

## EMERGENCY and FIRST AID PROCEDURES

**Inhalation** If respiratory discomfort or irritation occurs due to inhalation of oil mist, move person to fresh air. Vaporization is not expected at ambient temperatures. Contact a physician immediately if illness or adverse symptoms develop.

**Eye Contact** Immediately flush eyes with a large amount of cool, clean, low-pressure water while occasionally lifting and lowering eyelids. If irritation or adverse symptoms continues, seek medical attention. Thermal burns require immediate medical attention.

**Skin Contact** Remove contaminated clothing and wash affected skin area thoroughly with soap and water. Launder soiled clothing. If skin irritation develops or persists, seek medical attention.

**Ingestion** If material is swallowed and adverse symptoms develop, seek medical attention immediately. Induce vomiting only upon the advice of a physician. Never give anything by mouth to a person who is not fully conscious. If spontaneous vomiting is about to occur, place victim's head below knees. **Upon ingestion, there is a low to moderate risk of aspiration. Careful gastric lavage may be considered to evacuate large quantities of material.**

**Injection Injuries** - Subcutaneous injection is a medical emergency. Seek medical attention immediately. Inadequate treatment can result in ischemia and gangrene. Early symptoms may be

## SECTION 9

## CONTROL and PROTECTIVE MEASURES

minimal.

**Storage and handling** Store in an adequate ventilated area to control exposure. Special ventilation is necessary only if unusual operating conditions create mist concentrations in excess of the TLV. Avoid water contamination and extreme temperatures to minimize product degradation.

**Respiratory Protection** Not applicable for intended use. However, if unusual operating conditions create mist concentrations in excess of the TLV, an approved NIOSH/MSHA respirator is recommended.

**Eye Protection** Chemical face shield or protective goggles can reduce the possibility of accidental eye contact.

**Skin Protection** Impervious protection gloves can minimize skin exposures where prolonged or repeated exposures can occur.

**This is a general recommendation based upon general information as to normal uses and conditions. However when special or unusual uses or conditions exist, it is suggested that an expert assistance of an industrial hygienist be sought for special equipment.**

**SECTION 10****SPILL and LEAK PROCEDURES**

Take proper precautions to ensure your own health and safety before attempting spill control or clean up.

**Precautions if material is spilled or released**

Wear protective equipment and/or garments described in Section 9 if exposure conditions warrant. Shut off source, if possible and contain spill. Clean up spills as soon as possible. Absorb large spills with commercially available absorbent materials, such as absorbent clay or other dry inert materials. Keep out of water sources and sewers. Comply with all Federal, State, and Local regulations in reporting spill and cleanup. Provide adequate ventilation.

**Waste Disposal Method**

Place contaminated material in disposable containers. Material must be disposed of in accordance with Federal, State, and Local regulations. Contact the RCRA Superfund Hotline directly @ (800) 424-9346, a regional US EPA office, or a permitted waste management facility to provide guidance concerning case specific disposal issues.

]

**SECTION 11****REGULATORY INFORMATION****Comprehensive Environmental Response, Compensation and Liability Act  
(CERCLA) Section 102 Hazardous Substances**

As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically listed or designated as a hazardous substance.

**Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 313 - Toxic Chemicals**

This product does not contain greater than 1.0% of any chemical substance of Section 313 of Title III of Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

ComponentsCAS#Concentration %

**Section 311/312 - Hazard Categories**

This product may meet one or more of the criteria for the hazard categories defined in 40 CFR Part 370 as established by Sections 311 and 312 of SARA as indicated below.

|                                   |           |                 |           |
|-----------------------------------|-----------|-----------------|-----------|
| Immediate (Acute) Health Hazard   | <u>No</u> | Fire Hazard     | <u>No</u> |
| Delayed (Chronic) Health Hazard   | <u>No</u> | Reactive Hazard | <u>No</u> |
| Sudden Release of Pressure Hazard | <u>No</u> |                 |           |

**SECTION 11****REGULATORY INFORMATION**  
(continued)**Section 302 - Extremely Hazardous Substances**

This product is not known to contain any components in concentrations greater than one percent that are listed as Extremely Hazardous Substances in 40CFR Part 355 pursuant to the requirements of Section 302(a) of SARA.

**Clean Water Act (CWA)**

Under the CWA, discharge of crude oil and petroleum products to surface water without proper Federal and State permits must be reported immediately to the National Response Center at (800) 424-8802.

**RCRA Classification - Unadulterated Product as a Waste**

Prior to disposal, consult your Environmental contact to determine if TCLP (Toxicity Characteristic Leaching Procedure, EPA Test Method 1311) is required. Reference 40 CFR Part 261.

**Toxic Substances Control Act (TSCA)**

This product is in U.S. commerce, and listed in the TSCA Inventory of Chemicals; hence, it may be subject to applicable TSCA provisions and restrictions.

**Ecological Information**

Ecotoxicity - No data available.

Environmental Fate - Ecological effects testing has not been conducted on this product. However, plants and animals may experience harmful or fatal effects when coated with petroleum-based products. Petroleum-based (mineral) lube oils will normally float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen

depletion in the waterway might be enough to cause a fish kill or create an anaerobic environment.

## **SECTION 12**

## **LABELING**

### **NOTE**

This product has been determined not to be a physical or a health hazard as defined by the OSHA Hazard Communication Standard.

Avoid prolonged skin contact with used motor oil. Prolonged contact with used motor oil has been shown to cause cancer in laboratory animals.

After draining oil, wash skin thoroughly with soap and water. Clean oil-soaked clothing before reuse.

**SECTION 13****REFINED PETROLEUM OILS**

The products listed on page one of this MSDS contain one or more of the following base oils.

| <u>Chemical / Common Name</u>                | <u>CAS No.</u> |
|--|----------------|
| Solvent Refined, Heavy Paraffinic Distillate | 64741-88-4     |
| Solvent Refined Residuum                     | 64742-01-4     |
| Hydrotreated Heavy Paraffinic Distillate     | 64742-54-7     |
| Hydrotreated Residual Oils (Petroleum)       | 64742-57-0     |
| Hydrotreated Paraffinic Base Oil             | 64742-58-1     |
| Solvent Dewaxed Residual Oil                 | 64742-62-7     |
| Solvent Dewaxed, Heavy Paraffinic Distillate | 64742-65-0     |
| Hydrotreated Neutral Lubricating Oil         | 72623-87-1     |
| Hydrotreated Bright Stock Lubricating Oil    | 72623-83-7     |

This product is **FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.**

**SECTION 14****NOTES****DO NOT TAKE INTERNALLY**

Warco Products, Inc., believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. No warranty of fitness for any particular purpose, warranty of merchantability, or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and of the information referred to herein are beyond the control of Warco Products, Inc. Warco Products, Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.