



WARCO PRODUCT BULLETIN
WARCO GL-1
GEAR OIL
Revised 05.5.2008

www.warcopro.com

1 of 1

WARCO GL-1 GEAR OILS

PRODUCT BULLETIN

WARCO GL-1 GEAR OIL are manufactured from 100% virgin base oils. They provide long life for gears and bearings in the gear cases where OEM recommends the use of a straight mineral oil in SAE viscosity grades 90, 140, and 250 weights.

WARCO GL-1 GEAR OIL contain rust, corrosion and foam inhibitors, plus a pour depressant to assure fluidity of low temperatures. They are suitable for use where API Service Classification GL-1 is called for.

WARCO GL-1 GEAR OIL are recommended for use in transmissions, differentials, final drives, steering gears, universal joints, spline shafts, industrial closed gears and many other miscellaneous applications in bearing and gear lubrications of equipment where GL-1 or straight mineral oil is specified.

TYPICAL TEST DATA	90	140	250
Flash Point, COC, C° (F°)	245 (470)	246 (475)	248 (480)
Pour Point, C° (F°)	-12(10)	-11	-9
Specific Gravity, 60/60 F°	0.913	0.928	0.943
Gravity, API, 60 F°	23.4	21.0	18.7
Viscosity			
cSt @ 40°C	220	374	880
SUS @ 100°F	1100	2044	4550

Warco Products Inc.
12505 SW Herman Rd. .
Tualatin, OR 97062 USA

Tel: 01 503 783 0250
Fax: 01 503 612 1700
Email: sales@warcopro.com