



WARCO PRODUCT BULLETIN
WARCO OIL TREATMENT
Revised 03.01.2001

www.warcopro.com

1 of 1

WARCO OIL TREATMENT

PRODUCT BULLETIN

Warco Oil Treatment is a viscosity and wear additive for use in diesel and gasoline engines as well as transmissions. It supplements additives present in lubricating oil to restore performance to older engines. Provides good shear stability for use in motor oil, gear oil, and transmission fluid. Mixable with other aftermarket additives.

CUSTOMER BENEFITS:

Restores performance in older engines through:

- Restores compression and improves ring seal
- Reduces Oil Burning
- Reduces Friction

Reduces Smoking Exhaust

Lubricates moving parts under extreme conditions

Quiets valvetrain

Conditions oil seals

Antiwear component restores and provides additional protection for bearing surfaces and moving parts.

DIRECTIONS FOR USE:

Recommended dosage: One 15 US OZ can will treat a crankcase of 5 quarts. Basic treatment ratio is 3 ounces of Warco Oil Treatment per quart of crankcase capacity. Exceeding this ratio will not cause damage, but will not net a further increase in performance.

PHYSICAL SPECIFICATIONS:

| CHARACTERISTIC | MIN | MAX |
|---|-------|-------|
| GRAVITY: | | |
| Specific Gravity @60F/60F | .860 | .876 |
| Lb/US Gallon @ 60F | 7.16 | 7.29 |
| FLASH: (PMCC), F | 330 | ----- |
| Color: ASTM | 2.0 | 2.5 |
| Viscosity SUS@100F | 6,000 | 9,000 |
| Shear Stability Index (ASTM-3945) by Orbahn | 35 | ----- |

Warco Products Inc.
12505 SW Herman Rd. .
Tualatin, OR 97062 USA

Tel: 01 503 783 0250
Fax: 01 503 612 1700
Email: sales@warcopro.com