



Dexron®-VI Full Synthetic ATF

+1 (773) 376-9660 / www.warcopro.com / www.usglobalpetroleum.com

WARCO DEXRON®-VI Full Synthetic Multi-Vehicle Automatic Transmission Fluid is a full synthetic licensed DEXRON®-VI ATF (License Number: J-60189) and is the only GM® approved specification for vehicles of model years 2006 and newer. It is a high-performance universal ATF formulated from 100% synthetic base oils and an advanced additive package that meets or exceeds the performance, protection and service requirements of virtually all makes and models of passenger car and light truck automatic transmissions manufactured worldwide requiring a General Motors DEXRON®-VI or earlier generation DEXRON® fluids. It provides superior oxidation control, extended service intervals, maximum year-round low and high temperature protection, improved fuel economy, superior shear stability performance and offers consistent shift performance for the life of the fluid.

WARCO DEXRON®-VI Full Synthetic Multi-Vehicle Automatic Transmission Fluid is particularly recommended for use in GM 6-speed automatic transmissions and is fully backwards compatible with older GM automatic transmissions and may be used as a fluid top-off, or for drain-and fill or flush-and-fill installation or used in many power steering units and hydraulic systems. It recommended for a wide range of vehicles including use in most GM, Ford, Toyota, Honda vehicles and where GM DEXRON®-VI, DEXRON® III/III(H)/IIE, DEXRON® II, Ford MERCON® LV, Allison®, Honda® Z-1, Hyundai/Kia SP-II/III/IV, Toyota WS,T-III, T-IV, Mercedes Benz®, or Nissan® Matic Fluids are recommended.

Approvals, Applications and Benefits

- GM DEXRON®, DEXRON® II, II-E, III, III-G, III-H, VI • Ford MERCON®, MERCON® LV • Acura ATF-Z1
- Audi 5 HP LT71141 • Chrysler (Mopar) ATF-Plus, ATF +3, ATF +4 • Allison C-3, C-4, TES-295, TES-389
- CAT TO-2 • Daewoo LT 71141 • Esso LT 71141 • BMW • Honda Z-1 • Hyundai/Kia SP-II/III/IV • JASO
- FIAT T-IV type, JWS 3309 • Jaguar ATF 3403 M115, ATF LT71141, ZF 5HP24 • MINI COOPER T-IV
- ISUZU BESCO ATF-II /III • Mazda ATF D-II/M-III/M-V/FZ/S-1/N-1 • Shell 3403, M115, LA 2634
- Opel (all vehicles) • Peugeot ZF 4HP20 • Mercedes • Mitsubishi • Nissan/ Infinity Matic Fluids
- Toyota ATF D-II/D-III/T-III/T-IV/WS • VW 5 HP, G-055-025 A2 (JWS 3309) • Scion (all vehicles)
- Porsche ZF 5HP19FL, ZF 5HP20, LT71141 • Saab T-IV • Subaru ATF • Suzuki ATF • Volvo CE 97340
- Vickers M2950-S, I-286-S • Voith • ZF all 3 & 4 speed transmission • and many more
- Superior all-temperature, year-round protection and high performance
- Advanced anti-wear protection and shear stability
- Smoother shifting, protection against shudder
- Extended life of service and performance



Typical Characteristics - Dexron® VI ATF

GRADE	Test Method	DEXRON®-VI
Color	Visual	Red
Viscosity @ 100°C, cSt	ASTM D445	5.8
Viscosity @ 40°C, cSt	ASTM D445	29.5
Viscosity Index	ASTM D2270	145
Pour Point, °C/°F	ASTM D97	-51 / -59.8
Flash Point, COC °C/°F	ASTM D92	220 / 428
API Gravity	ASTM D1298	36.0
Brookfield Vis.cP @ -40°C	ASTM D2983	10,000

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.



MADE IN USA

V200109



HANDLING AND SAFETY INFORMATION - Refer to WARCO (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.